


SAPPHIRE® COMPACT Direct Low Pressure Automatic Fixed Fire Suppression System

Description

- Automatic and quick-acting pneumatically actuated fire suppression system (nominal charge of 15 bar (218 psi)) utilizing 3M™ Novec™ 1230 Fire Protection Fluid
- LPS 1666 Certified
- Protects enclosures with vents or forced air ventilation
- Requires no power supply for detection or actuation, remaining operational during power interruptions
- Can protect up to four enclosures with one system
- Highly reliable detection tube, unaffected by dirt, dust, debris, or oil

This schematic shows a typical installation. The design and installation should be completed in accordance with the HYGOOD® SAPPHIRE® COMPACT manual (Part No.14A-50H, latest revision).

If multiple enclosures are being protected, the risk assessment must assume that a fire can occur in only one protected enclosure at one time.



E000663

Ordering Information

| Item | Description | Part No. | Quantity (based on typical schematic above) |
|------|---|-----------|---|
| 1 | SAPPHIRE COMPACT container assembly with 2 kg (4.4 lb) Novec 1230 fluid | 303150001 | 1 |
| | SAPPHIRE COMPACT container assembly with 2.5 kg (5.5 lb) Novec 1230 fluid | 303150002 | |
| | SAPPHIRE COMPACT container assembly with 3 kg (6.6 lb) Novec 1230 fluid | 303150003 | |
| 2 | Detection tube (red) | 304150013 | 10 m (32.8 ft) |
| 3 | End-of-line adaptor with pressure gauge | 304150010 | 1 |
| 4 | Pressure gauge with switch contact (standard) (Contacts closed at nominal charge pressure) | 302150001 | 1 |
| | Pressure gauge with switch contact (optional) (Contacts open at nominal charge pressure) | 302150002 | |
| 5 | Grommet - detection tube | - | 1 |

- Notes:**
1. The pressure gauge with switch contact and bracket are included within the container assembly part number.
 2. LPS 1666 is limited to enclosures having a maximum volume of 2 m³.
 3. Part No. 304150013 quantity is dependent on the fire risk within the enclosure and design assessment by the system designer or installer.
 4. Container design in accordance with EN3.

Safety Data Sheets (SDS) are available at www.hygood.com

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

3M and Novec are trademarks of 3M Company.

HYGOOD, SAPPHIRE, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.